

SPECIFICATIONS

MODEL AMW/AMC			25		30		45		60	
			Indoor	Outdoor	Indoor	Outdoor	Indoor	Outdoor	Indoor	Outdoor
Capacity (50 / 60 Hz)	Cooling	BTUH	9000 / 9000		12000 / 12200		18400 / 19200		22700 / 23600	
	Heating	BTUH	9700 / 10300		12500 / 12700		18800 / 19700		23400 / 24300	
Airflow (50 / 60 Hz)		CFM	265 / 275		310 / 320		400 / 420		510 / 530	
Electrical		V / Ph / Hz	220-240 / 1 / 50 or 208 - 230 / 1 / 60							
Input power (50 / 60 Hz)	Cooling	W	890 / 940		1230 / 1250		1830 / 1850		2350 / 2380	
	Heating	W	920 / 960		1300 / 1320		1880 / 1900		2380 / 2410	
Running Current	Cooling	A (50 / 60)	4.4 / 4.5		6.0 / 6.1		8.6 / 8.9		11.4 / 11.8	
	Heating	A (50 / 60)	3.7 / 3.6		6.3 / 6.4		8.7 / 8.9		11.2 / 11.6	
Fan Motor	Type		Resin type							
Noise Level		dBA	35	48	37	49	38	50	39	51
Compressor	Type		Rotary							
Refrigerant Control			Capillary tubes							
Evaporator			Slit fin with inner groove tubes							
Refrigerant			R-22							
Refrigerant Connection	Liquid	Inches	1/4		1/4		1/4		3/8	
	Suction	Inches	3/8		1/2		5/8		5/8	
Drain Connection		Inches	5/8		5/8		5/8		5/8	
Dimension	Height	Inches	9.85	18.90	10.79	21.93	12.60	25.43	12.60	25.43
	Width	Inches	29.33	23.22	31.10	25.59	39.92	31.50	39.92	32.40
	Depth	Inches	7.48	10.24	7.48	9.84	7.48	9.92	7.48	10.87
Weight		Lbs	15	52	26	77	35	110	36	132
Container loading 20' / 40'		sets	104 / 210		100 / 204		66 / 132		66 / 132	

Note:

1. = Nominal capacities rated according to ARI 240 and DOE test conditions; Capacities are based on 80 / 67° F DB / WB indoor and 95° F outdoor ambient temperature.
2. = Heating capacities are based on 70 / 60° F DB / WB indoor and 47° F outdoor ambient temperature.

Due to constant improvement, all specifications subject to change without notice

FEATURES

- ❑ Sleek and compact design, matches virtually any room layout.
- ❑ Its lightweight design makes installation easy.
- ❑ Powerful cooling and heating capabilities with compact design
- ❑ Ultra quiet operation.
- ❑ Built-in electrical protection, including 3 minute time delay, high and low voltage cut-off protection.
- ❑ Auto swing mechanism, activated by remote control, ensures even air distribution.