

'M' Series Multi-Flex

Dual Zone Outdoor Units			
	Cooling	Heat Pumps	
OUTDOOR UNIT	A-MMC24FA-1	A-MMH18FA-1	A-MMH24FA-1
Power Supply	208/230-1-60	208/230-1-60	208/230-1-60
System Cooling Cap. (BTUH)	18,000–24,000	18,000	18,000–24,000
Cooling Amps	10.1	8.8	10.1
SEER	13*	13*	13*
System Heating Cap. (BTUH)	N/A	18,000	18,000–24,000
Heating Amps	N/A	8.6	9.7
HSPF	N/A	7.6	7.6
Outdoor Unit Dimensions			
Width (inches)	34.3	34.3	34.3
Height (inches)	31.8	25.8	31.8
Depth (inches)	12.6	12.6	12.6
Net Wt/Shipping Wt (lbs)	141.1/151.9	125.7/134.7	141.1/151.9
Electrical Data Outdoor Unit**			
Main Pwr. Connection	Outdoor Unit	Outdoor Unit	Outdoor Unit
Min. Circuit Ampacity	20	15	20
Max. Fuse/HACR Cir. Brkr	25	20	25
Recommended Indoor/ Outdoor Connecting Cable Type (SJOW)	See note**	See note**	See note**
Line Sets O.D. (in.) / Refrigerant			
Liquid (Flare)	1/4	1/4	1/4
Suction (Flare)	3/8	3/8	3/8
Max Length	50 ft.	50 ft.	50 ft.
Max. Elevation (Outdoor)	25 ft.	25 ft.	25 ft.

Tri-Zone Outdoor Units		
	Cooling	Heat Pump
FEATURES	A-MMC36FA-1	A-MMH36FA-1
Power Supply	208/230-1-60	208/230-1-60
System Cooling Cap. (BTUH)	27,000–36,000	27,000–36,000
Cooling Amps	16.6	16.6
SEER	13*	13*
System Heating Cap. (BTUH)	N/A	27,000–36,000
Heating Amps	N/A	15
HSPF	N/A	7.6
Outdoor Unit Dimensions		
Width (inches)	34.3	34.3
Height (inches)	40.7	40.7
Depth (inches)	12.6	12.6
Net Wt/Shipping Wt (lbs)	185.2/201.5	185.2/201.5
Electrical Data Outdoor Unit**		
Main Pwr. Connection	Outdoor Unit	Outdoor Unit
Min. Circuit Ampacity	30	30
Max. Fuse/HACR Cir. Brkr.	40	40
Recommended Indoor/ Outdoor Connecting Cable Type (SJOW)	See note**	See note**
Line Sets O.D. (in.) / Refrigerant		
Liquid (Flare)	1/4	1/4
Suction (Flare)	3/8	3/8
Max. Length	50 ft.	50 ft.
Max. Elevation (Outdoor)	25 ft.	25 ft.

Multi-Flex Indoor Units				
Indoor Unit	B-MMC09FA-1	B-MMH09FA-1	B-MMC12FA-1	B-MMH12FA-1
Cooling Cap. (BTUH)**	9000	9000	12,000	12,000
Heating Cap. (BTUH)**	N/A	9000	N/A	12,000
Air Flow (CFM H/ML)**	289/271/254	289/271/254	332/314/296	332/314/296
Fan Speeds	4 / - / 3	4 / 3 / 3	4 / - / 3	4 / 3 / 3
Dehumidify (Pts/Hr.) per zone	2.3	2.3	2.5	2.5
Air Direction (4-Way)				
Vertical Modulating	Remote	Remote	Remote	Remote
Horizontal (left/right)	Manual	Manual	Manual	Manual
Random Swing	Standard	Standard	Standard	Standard
Indicator Lamps				
ON/OFF	Standard	Standard	Standard	Standard
24 Hr. Timer/Sleep Mode	Standard	Standard	Standard	Standard
Defrost or Hot Start	N/A	Standard	N/A	Standard
Temperature Setting	Standard	Standard	Standard	Standard
Indoor Unit Dimensions				
Width (inches)	33	33	35.2	35.2
Height (inches)	10.6	10.6	11.1	11.1
Depth (inches)	6	6	6.5	6.5
Net Wt/Shipping Wt (lbs)	15.4/18.1	15.4/18.1	20.5/24	20.5/24

* Applies when indoor and outdoor units have equivalent capacities.
**Always follow local, state and national codes.



Warranty—5 years on compressor, 1 year on parts
(Some limitations apply; see printed warranty for details.)